

JANCIS IR interactive display technical specification				
Display	Model no.	SL-M06503	SL-M07503	SL-M08603
	Bonding	Zero-gap	Zero-gap	Zero-gap
	Size	65 inch	75 inch	86 inch
	Backlight	Direct	Direct	Direct
	Display area (mm)	1428.48(H) x 803.52(V)	1649.664(H) x 927.936(V)	1895.04(H) x 1065.96(V)
	Aspect Ratio	16:9	16:9	16:9
	Viewing Angle(V/H)	178°	178°	178°
	Brightness	400 nits	400 nits	400 nits
	Contrast ratio	5000:1	5000:1	5000:1
	Colors	1.07B(10 bits)	1.07B(10 bits)	1.07B(10 bits)
	Resolution	3840 x 2160	3840 x 2160	3840 x 2160
	Refresh Rate	60HZ	60HZ	60HZ
	Response time (Grey to grey)	≤7ms	≤7ms	≤7ms
	Glass	4mm, Anti Glare, tempered, Anti-Finger print and Antimicrobial coating,< Mohs7		
Android	Side bar	Yes, both sides		
	Ambient light sensor	Support		
	Lifetime	≥50,000h		
	Mainboard / Chip	RK3576	RK3576	RK3576
	CPU	A72*4+A53*4	A72*4+A53*4	A72*4+A53*4
	GPU	G52 MC3	G52 MC3	G52 MC3
Touch	RAM	16G DDR4	16G DDR4	16G DDR4
	ROM	256G	256G	256G
	Android version	14 EDLA Certification	14 EDLA Certification	14 EDLA Certification
	Sensor type / Recording technology	Infrared touch screen		
	Touch / Writing points	40 points / 20 points	40 points / 20 points	40 points / 20 points
	Minimum Touch Object	2mm	2mm	2mm
Buttons	Precision	±1mm	±1mm	±1mm
	Touch screen resolution	32,768 x 32,768 pixels	32,768 x 32,768 pixels	32,768 x 32,768 pixels
	Touch response time	≤5ms	≤5ms	≤5ms
	Writing instruments	passive pen, fingers and other opaque objects		
	Front buttons	Eye protection/Setting/Return/Source/Home/V-/V+/Power		
	Touch-USB	1 Type-B	1 Type-B	1 Type-B
Front interface	HDMI IN (2.0)	1	1	1
	Type-C	1 (Multimedia, 65W)	1 (Multimedia, 65W)	1 (Multimedia, 65W)
	USB (3.0)	2	2	2
	HDMI Out	1	1	1
	HDMI IN (2.0)	2	2	2
	DP In	1	1	1
Rear interface	Type-C 3.0	1(15W)	1(15W)	1(15W)
	Touch USB 3.0	1	1	1
	Public USB-A 3.0	1	1	1
	Android USB	2	2	2
	VGA IN	1	1	1
	VGA LINE IN	1	1	1
	Line Out	1(3.5mm)	1(3.5mm)	1(3.5mm)
	Mic In	1(3.5mm)	1(3.5mm)	1(3.5mm)
	SPDIF OUT	1(optical)	1(optical)	1(optical)
	RJ45 IN	1(1000M)	1(1000M)	1(1000M)
	RJ45 Out	1(1000M)	1(1000M)	1(1000M)
	RS232	1	1	1
	TF Card	1 (Max 256G)	1 (Max 256G)	1 (Max 256G)
Wifi & BT	WIFI & Bluetooth	WIFI6 + BT5.2		
Speakers	Speakers	20W x 2		
	Camera (optional)	4K / UHD (3840 x 2160 pixels) 13M pixel, 30 fps 10M, support AI		
	Microphone (optional)	Built-in 8 array mic, 10m Sound pick up		
Power consumption	Power consumption	≤126 W	≤143 W	≤175W
	Standby	≤0.5W	≤0.5W	≤0.5W
	Working voltage	100-240V~ 50/60Hz	100-240V~ 50/60Hz	100-240V~ 50/60Hz
Packing	In the box	Magnetic digital stylus x 2 / Remote x 1/ Power cable x 1/ HDMI cable x 1/ Touch USB cable x 1/Warranty card x 1/Wall mount x 1		
VESA	VESA size	500 x 400mm	600 x 400mm	800 x 400mm
Warranty	Warranty	36 month	36 month	36 month
	Declarations of conformity	CE / EMC / LVD / RED / RoHS / Energy Star		
Dimension	Physical dimension(mm)	1488.7 x 895.3 x 94.1	1710.8 x 1018.9 x 94.1	1957 x 1158.6 x 94.1
	Packed dimension(mm)	1626 x 1036 x 210	1848 x 1159 x 210	2094 x 1299 x 210
	NW	43±1KG	55±1KG	69±1KG
	GW	55±1KG	69±1KG	89±1KG